



Indoor Full Color LED Video Wall

TV-COB127-Y



Description:

It features seamless splicing, high contrast, high color gamut, ultra-high color consistency, high grayscale, fast frame changing speed, natural color reproduction, wide viewing angle, perfect display, long service lifespan and other characteristics. It is shockproof, crashproof, moisture-proof, front waterproof, dust-proof, and is suitable for use in various harsh environments, with better high and low temperature/humidity storage and application performance.

Feature:

- *High protection: shockproof, crashproof, moisture-proof, front waterproof and dust-proof.
- *High adaptability: suitable for various harsh environments, with better high and low temperature/humidity storage and application performance.
- *High reliability: realize ultra low failed rate during long-term use. Even if individual lamp bead fails, the modules can be directly replaced and returned to the factory for maintenance to prevent the trouble of repairing the lamp during long-term use for users.
- *It can be used for real-time scene monitoring, various advertising playback.
- *It is seamlessly spliced without visual black seams at all.
- *The display module is flexible, and supports flat and curved smooth splicing.
- *DC low voltage power supply; natural heat dissipation, no fan and no operation noise.
- *Ultra-low cabinet failed rate, extremely low maintenance and use costs, and easy replacement of unit boards.
- *Support picture correction. The Gamma correction adopted enables pixel-by-pixel brightness color correction.
- *Support intelligent light control, intelligent brightness adjustment, improve picture comfort, more energy saving and power saving
- *With ultra-wide viewing angle display, the display screen has a wider visual range, and the viewing picture from any angle is still clear.
- *With ultra-high refresh rate, good picture coherence and high fluency.
- *The picture is delicate and realistic, and the grayscale is still excellent under low brightness.
- *Support ultra HD display. Unique image quality enhancement technology effectively improves image clarity, making high-speed picture smooth without image smearing.
- *Support integrating 3D, touch screen, somatosensory games and other functions to improve entertainment and interactivity.

Specifications:

Model	COB1.27
Pixel pitch	1.27mm
Resolution	620001 pixels/m ²
Lamp bead/IC	COB/professional high refresh IC
Pixel composition	1R1G1B
Module resolution	120*90
Module dimension(mm)	152.4*114.3
Cabinet resolution	480*270
Cabinet dimension(mm)	609.6*342.9
Cabinet weight	4.7kg/pc
Operating voltage	DC +4.2V~+5V
Best viewing distance	≥3.8m
Horizontal view angle	≥160°
Vertical view angle	≥160°
Maintenance method	Front maintenance/rear maintenance
Graphics card	DVI/HDMI/DP
Video signal	Compatible with PAL/NTSC/SECAM format, support S-Video; VGA; RGB; Composite Video; SDI; DVI; RF; RGBHV; YUV; YC, etc.
Control mode	Synchronous control
Drive device	Constant current drive
Refresh rate	≥3840Hz
Frame rate	≥60Hz
Scanning method	30S
Brightness	≥600CD/m ² (adjustable)
Grayscale	12/14/16bit
Contrast	≥10000:1
Attenuation rate (after 3-year work)	≤15%
Brightness adjustment method	Auto/Manual: 1~100%
Computer operating system	WIN98/2000/WIN XP/VIN Vista/WIN7
MTBF	≥10000H
Lifespan	100000H
Failed rate	≤1/100000 and no continuous failed pixels
Software	Professional LED video wall system programming software
Storage temperature	-35°C~+85°C
Operating temperature	-10°C~+40°C
Operating voltage(AC)	220V±10%/50Hz or 110V±10%/60Hz
Average power consumption	≤200W/m ²
Maximum power consumption	≤600W/m ²
Cabinet specification	Die-cast aluminum cabinet
Brightness uniformity	≥98%
Protection class	Front IP54